

JIMS

Station for boresight large multi-sensor systems



Fig. 1. Photo of the JIMS800 boresight station



Fig. 2. Exemplary large multi sensor EO systems that can be tested using JIMS

BASIC INFORMATION:

JT stations are Inframet main product for boresight of multi-sensor imaging/laser systems. These stations are image projectors combined with a set of laser image sensors that can be used to align almost all EO surveillance systems to a reference optical axis, a reference mechanical axis, or a reference mechanical plane. These stations enable high accuracy boresight because all sensors can see the same image projector/receive optics.

Aperture of on-axis reflective collimator used as image projector is the main limiting factor of JT stations and determines if the station can be used for boresight of a specific EO system. It is required that collimator aperture overlaps at least 50% of area of every optical sensors of tested EO system. It means that collimators of extremely big aperture are needed to test EO systems where thermal imager is separated by long distance from other imaging/laser sensors.

Inframet manufactures JT boresight stations built using on-axis reflective collimators of aperture up to 600mm. JT600 station is a station built using a very big collimator and enables boresight of great majority of multi-sensor EO systems. However, there are on-market EO systems for long distance surveillance built using big imaging/laser sensors separated from each other up to 1000mm. Such rare EO systems cannot be tested using biggest of typical JT station: the biggest is the JT600 station.

JIMS boresight stations can be treated as a special modified version of JT station optimized for testing EO systems of ultra large aperture up to 1000mm. From design point of view JIMS is practically a typical JT400 station with additional block called CEB collimator expander block. This block can increase apparent collimator aperture up to 1000mm in one direction (typically horizontal). However, it should be noticed that boresight accuracy using JIMS station is slightly worse (about 0.2mrad) comparing to boresight accuracy using typical JT station (below 0.1mrad) because the CEB block generates a small internal boresight error. Anyway JIMS can be considered as a near perfect budget saving solution for boresight of ultra large EO surveillance systems having the imaging/laser sensors located on a large horizontal platform.

JIMS

Station for boresight large multi-sensor systems

VERSIONS

The basic division of JIMS station is based on maximal acceptable distance between centers of optics of two sensors of tested EO system that can be tested. This distance is indicated by number after JIMS letters (see Table 1).

Table. 1. Division of JIMS stations based on the maximal distance

Aperture code	Max distance between centers of optics of two sensor of tested EO system
JIMS 600	600 mm
JIMS700	700mm
JIMS 800	800 mm
JIMS900	900mm
JIMS 1000	1000 mm

The digit code gives information about max distance between centers of two sensor of EO system that can be tested. There are also other criterion used to describe more JIMS station: computerization, boresight capabilities, testing capabilities, list of blocks.

Table. 2. Versions of JIMS system

Code	Computerization/Boresight/test capabilities	Modules
X1	Non computerized test system Boresighting of typical set of imaging systems (thermal imagers, VIS cameras, optical sights) Test range: measurement of resolution of VIS-NIR cameras and thermal imagers	CJT40180 on axis reflective collimator, DNLCB dual color blackbody, CDNLCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block
X2	Non computerized test system Boresighting of typical set of imaging systems (thermal imagers, VIS-NIR cameras, optical sights) and mono-pulse laser range finders Test range: as mentioned as in X1	CJT40180 on axis reflective collimator, DNLCB dual color blackbody, CDNLCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block, basic LSC1 set of laser sensing cards, SOA set of optical attenuators and holder
X3	As in level X2 but multipulse LRF and laser pointers can be aligned too.	CJT40180 on axis reflective collimator, DNLCB dual color blackbody, CDNLCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block, expanded LSC2 set of laser sensing cards, SOA set of optical attenuators and holder
Y1	Computerized test system Boresighting of typical set of imaging systems (thermal imagers, VIS-NIR cameras, optical sights), mono-pulse laser range finders and laser pointers. Test range of imaging systems: measurement of resolution of VIS-NIR cameras/optical sights, and of thermal imagers.	CJT40180 on axis reflective collimator, DNLCB dual color blackbody, CDNLCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block, basic LSC1 set of laser sensing cards, SOA set of optical attenuators and holder, PC set (or laptop), analog frame grabber (optional digital grabber), BOR computer program
Y2	As per level Y1 but multipulse LRFs and laser pointers can be aligned, too.	CJT40180 on axis reflective collimator, DNLCB dual color blackbody, CDNLCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block, expanded LSC2 set of laser sensing cards, SOA set of optical attenuators and holder, PC set (or laptop), analog frame grabber (optional digital grabber), BOR computer program
Y3	As in Y2 but optical axis of the station can be aligned perpendicular to reference mechanical plane of platform where tested system is fixed.	As in Y2 but BRM camera, ABT boresight target and REP reference plane (BORIM boresight set) are included
Y4	As per level Y3 but divergence angle of tested LRFs can be accurately measured.	As in Y3 but SR10 camera and modified BOR software are delivered.

JIMS

Station for boresight large multi-sensor systems

OPTIONS:

1. Any version of JIMS station can be expanded to test and boresight of SWIR imager. Please add letter *S* to chosen version.
2. JIMS can be used on any large, stable optical table delivered by customer. However, Inframet can deliver optionally a large AT series optical table to work as platform for both JIMS station and the tested system. Please add option AT.
3. Inframet can deliver optionally an AT optical table to work as platform for JIMS station and additional MT mobile table to work as platform for the tested system. Please add option MAT.
4. Inframet can deliver optionally frame grabber and software to capture video images from digital camera of interface from this list: Camera Link, GigE, LVDS, HD-SDI/DVI/HDMI, AHD/HD-TVI/HD-CVI, CoaXPress, USB2.0, USB3.0, Ethernet. Please add option GRAB.

SUMMARY:

To summarize, version of JIMS system is described by a code composed from two components: three/four digit aperture code shown in Table 1; and letter/digit test capabilities code shown in Table 2.

Example **JIMS 800-Y4** means JIMS system of following features:

1. maximal acceptable distance equal to 800mm
2. type of system: computerized,
3. boresighting capabilities: thermal imagers, VIS-NIR cameras, mono-pulse laser range finders, multi-pulse laser range finders, designators, pointers, and to a reference mechanical plane of the platform
4. test range: measurement of resolution of VIS-NIR cameras/optical sights, and of thermal imagers. Measurement of divergence angle of LRFs, designators, and laser pointers.

Blocks of JIMS800-Y4 are: CJT40180 on axis reflective collimator, DNCCB dual color blackbody, CDNCCB controller, power supply, set of targets, set of CEB expanders, CEBH holder of expander block, expanded LSC2 set of laser sensing cards, SOA set of optical attenuators and holder, PC set (or laptop), analog frame grabber (optional digital grabber), BOR computer program, BRL camera, ABT boresight target, REP reference plane.

In case of any problems with choosing suitable version of JIMS boresight system please send Inframet detail information about multi-sensor system to be aligned and tested. Inframet engineers then choose version of JIMS system optimal for your application.

Version: 7.2

CONTACT:

Tel: +48 22 6668780

Fax: +48 22 3987244

Email: info@inframet.com